Safety Data Sheet



according to OSHA Hazard Communication 29 CFR Part 1910.1200

Section 1. Identification

Product Information:	72Y-A044
Product Name:	YELLOW FAST DRY 1952E TYPE 1
Recommended Use:	Liquid Paint
Application Method:	Latex Surface Paint
Supplied by:	Aexcel Corporation 7373 Production Drive. Mentor, OH 44060
Emergency Telephone:	Chemtrec: 800-424-9300
Safety Data Sheet Coordinator:	IWebb@AexcelCorp.com

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Skin and eye irritant.

GHS Classification Repr. 1A, STOT SE 1

Symbol(s) of Product



Signal Word Danger

(

GHS HAZARD STATEMENTS			
Reproductive Toxicity, category 1A	H360	May damage fertility or the unborn child.	
STOT, single exposure, category 1	H370	Causes damage to organs . Classified Category 1 Substances that produced significant toxicity in humans and evidence to produce significant toxicity with single exposure. Cell death, adverse change in biochemistry, haematology or urinalysis parameters, Central or peripheral nervous system and effects senses. multifocal or diffuse necrosis, fibrosis or granuloma formation in organs.	
GHS LABEL PRECAUTIONARY STA	TEMENTS		
P201	Obtain spe	cial instructions before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No		
	smoking.		
P233	Keep conta	ainer tightly closed.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.		
P264	Wash thoroughly after handling.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P307+P311	IF exposed	d: Call a POISON CENTER or doctor/physician.	

P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local rules and regulations.
GHS SDS PRECAUTIONARY STAT	EMENTS
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do no eat, drink or smoke when using this product.

Section 3. Composition/Information on ingredients

<u>Chemical Name</u>	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
METHANOL	67-56-1	1.0-2.5	GHS02-GHS06-	H225-301-311-319-331-360-370
			GHS08	

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air. Oxygen or artificial respiration if needed.

FIRST AID - SKIN CONTACT: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Wash off with soap and water.

FIRST AID - EYE CONTACT: Flush eye(s) immediately with plenty of water. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

FIRST AID - INGESTION: Induce vomiting immediately and call a physician.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

SPECIAL FIREFIGHTING PROCEDURES: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Section 7. Handling and storage



HANDLING: Containers of this material may be hazardous when emptied. All metal parts of the mixing and processing equipment must be grounded. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not reuse empty containers. Keep away from food and drink. Keep away from open flames, hot surfaces and sources of ignition.

STORAGE: Harmful - Store away from foodstuffs.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits					
<u>Chemical Name</u>	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING	
METHANOL	200	250	200	NA	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection

RESPIRATORY PROTECTION: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.



HYGIENIC PRACTICES: General industrial hygiene practice.

9. Physical and Chemical Properties

65 - 482		Vapor D	ensity:	1.1	1	
Characteristic		Odor Th	reshold:	NA		
Heavy Yellow Lic	quid	Evapora	tion Rate:	5.2	0	
NE		Specific	Gravity:	1.5	12	
NA		pH:		NA		
47.30				NA		
Liquid		Flash Po	oint, °C:	95,	°F 203	
viation legend)						
VAPOR DENSITY	EVAPORATIO	N RATE	BOILING PC	<u>DINT</u>	<u>VP mmHg</u>	<u>at DEG. F</u>
1.11	5.2		149		47.3	77
,	Heavy Yellow Lie NE NA 47.30 Liquid riation legend) <u>VAPOR DENSITY</u>	Heavy Yellow Liquid NE NA 47.30 Liquid riation legend) <u>VAPOR DENSITY</u> <u>EVAPORATIO</u>	Characteristic Odor Th Heavy Yellow Liquid Evapora NE Specific NA pH: 47.30 Viscosit Liquid Flash Por iation legend) VAPOR DENSITY EVAPORATION RATE	Characteristic Odor Threshold: Heavy Yellow Liquid Evaporation Rate: NE Specific Gravity: NA pH: 47.30 Viscosity: Liquid Flash Point, °C: viation legend) VAPOR DENSITY	CharacteristicOdor Threshold:NAHeavy Yellow LiquidEvaporation Rate:5.2NESpecific Gravity:1.5'NApH:NA47.30Viscosity:NALiquidFlash Point, °C:95,viation legend)VAPOR DENSITYEVAPORATION RATEBOILING POINT	Characteristic Odor Threshold: NA Heavy Yellow Liquid Evaporation Rate: 5.20 NE Specific Gravity: 1.512 NA pH: NA 47.30 Viscosity: NA Liquid Flash Point, °C: 95, °F 203 viation legend) VAPOR DENSITY EVAPORATION RATE BOILING POINT VP mmHg

Section 10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Do not breathe vapours or spray mist.

INCOMPATIBILITY: Incompatible with strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if stored and applied as directed.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause intense irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Direct skin contact may cause moderate to severe irritation and possibly dermatitis. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: possible risk of irreversible effects if swallowed. May be fatal or cause blindness.

CARCINOGENICITY: No Information

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	<u>Oral LD50</u>	Dermal LD50	Vapor LC50
67-56-1	METHANOL	5600	15800	N.I.

N.I. - No Information

Section 12.	Ecological	information
-------------	------------	-------------

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

Section 13. Disposal considerations



Product

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping DOT Technical Name: DOT Hazard Class: DOT UN/NA Number:

Paint, Latex Paint Non-Hazardous Not Regulated Packing Group: Hazard SubClass: Resp. Guide Page: Non-Regulated No Information No Information

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

67-56-1

Fire Hazard, Acute Health Hazard

SARA SECTION 312:	
Chemical Name	CAS-No.

METHANOL

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
METHANOL	67-56-1
AMMONIA	7664-41-7
ETHYLENE GLYCOL	107-21-1

TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
CALCIUM CARBONATE	1317-65-3
WATER	7732-18-5
ACRYLIC POLYMER	

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	<u>CAS-No.</u>
CALCIUM CARBONATE	1317-65-3
WATER	7732-18-5
ACRYLIC POLYMER	

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical</u>	Name				
METHANOL					

CAS-No. 67-56-1

International Regulations: As follows -

CANADIAN WHMIS:

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

Section	16. Other i	nformation, inc	luding date	of preparation	on of the l	ast revision			
Revision Date: Reason for revision:		6/4/2015 GHS			Supercedes Date:		New MSDS		
Datasheet produced by:		Regulatory Department							
HMIS Rati	ngs:								
Health:	1	Flammability:	1	Reactivity:	0	Personal Protection:	Х		
	ganic Compo HS Hazard S	ounds, gr/ltr: tatements shown i	94 n Section 3 de		ngredient:				
H225		Highly flammable liquid and vapour.							
H301		Toxic if swallowed.							
H311		Toxic in contact with skin.							
H319		Causes serious eye irritation.							
H331		Toxic if inhaled.							
H360		May damage fertility or the unborn child.							

Causes damage to organs . Classified Category 1 Substances that produced significant toxicity in humans and evidence to produce significant toxicity with single exposure. Cell death, adverse change in biochemistry, haematology or urinalysis parameters, Central or peripheral nervous system and effects senses. multifocal or diffuse necrosis, fibrosis or granuloma formation in organs.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information

H370