



**Rapid Dry**  
**Fast Dry Sealer Additive**

**TECHNICAL BULLETIN**

**Description:**

**Rapid Dry** is a proprietary blend of special copolymers and additives that has been specifically designed to reduce the drying time of all types of pavement sealers. **Rapid Dry** reduces the curing time, improves adhesion and flexibility and reduces scuffing and power steering marks in all pavement sealers, when used as directed.

**Mix Designs:**

The following chart provides guidelines for the use of **Rapid Dry** with Brewer Cote® in a two coat application. For information on use with other products or with a third coat, please consult the mix design section of the Technical Data Bulletin for the specific product.

Low Traffic	1st Coat	2nd Coat
Brewer Cote® - Gallons	100	100
Water - Gallons	40 - 55	35 - 50
<b>Rapid Dry</b> - Gallons	2 - 3	2 - 3
Aggregate - Pounds	0 - 200	100 - 200
Moderate Traffic		
Brewer Cote® - Gallons	100	100
Water - Gallons	40 - 55	35 - 50
<b>Rapid Dry</b> - Gallons	3 - 4	3 - 4
Aggregate - Pounds	0 - 300	100 - 300
Heavy Traffic		
Brewer Cote® - Gallons	100	100
Water - Gallons	40 - 55	35 - 50
<b>Rapid Dry</b> - Gallons	4 - 5	4 - 5
Aggregate - Pounds	0 - 400	100 - 400

**Usage:**

Using the mix design chart above, determine the correct amount of **Rapid Dry** to be added to the pavement sealer. Add the sand and then, while continuously agitating the pre-diluted pavement sealer, slowly pour **Rapid Dry** into the sealer.

Continue agitating the mixture until a uniform consistency is achieved.

**Rapid Dry** will thicken sealer only slightly, there is no need to dilute it with water prior to adding to sealer.

**Key Advantages**

- **Significantly** reduces curing time
- Improves aggregate bonding
- Speeds drying time with rapid film strength development
- Reduces scuffing and power steering marks
- Improves flexibility

**Rapid Dry Typical Properties:**

Property	Typical
Non-Volatile, %	34 - 40
Ash, %	0.1 - 0.5
pH	7.0 - 10.0
Particle size, microns	< 0.5
Wt/gal, lbs.	8.2 - 8.5
VOC maximum, grams/liter	5
Color, wet	Blue white

**Precautions:**

**Rapid Dry** may cause minor skin irritation. As with all chemicals, wear splash resistant goggles, protective gloves and clothing when handling. In case of skin or eye contact, immediately flush the area with clean water. Consult Material Safety Data Sheet for more information on safety and handling.

**Keep out of reach of children**  
**For exterior use only**  
**Close container when not in use**

**Non-flammable**  
**Protect from freezing**

**Packaging:**

5 gallon pails and 55 gallon drums

**Limited Warranty:**

The Brewer Company warrants this product to be of merchantable quality when stored, used, and applied in accordance with the specifications and instructions herein. This Limited Warranty represents the sole and exclusive warranty. The Brewer Company's liability under this Limited Warranty is limited to replacement of the product proven defective, or at its option, refund of the purchase price.