



ProBond
Primer for Asphalt Surfaces

TECHNICAL BULLETIN

Description:

ProBond will improve adhesion of pavement sealer to any asphalt surface. It is a unique waterborne primer designed to form a strong bond to asphalt pavements for application of refined tar or asphalt emulsion sealers. *ProBond* is able to penetrate minor surface films of hard to clean materials such as tree sap and adhere to the underlying pavement.

ProBond can also be used to treat oil and gasoline stains on asphalt pavement. It will bond to the surface and helps prevent oil and gasoline residue from bleeding through freshly applied sealer.

Usage:

Surface must be free of dirt, dust and other contaminants. Any build up of sap, oil or grease must be removed prior to application. Scrapers, wire brushes and torches can all be used to remove oil or grease residue. Scrubbing with soap and water using street brooms or pressure washing will help insure bonding to surfaces contaminated with tree sap. Cleaned areas must be thoroughly rinsed prior to application. *ProBond* is not a replacement for proper cleaning. All visible tree sap residue must be removed prior to application.

ProBond, as supplied, is ready to use. It may be diluted with clean, potable water up to 35% by volume.

Apply mixed *ProBond* by roller, brush or spray. Rollers must have a minimum of 3/8 inch nap.

Allow to dry completely prior to application of pavement sealer.

Apply only when ambient and pavement surface temperatures are a minimum of 50° F. during and for at least twenty-four (24) hours after application.

Coverage:

One gallon of undiluted *ProBond* will cover approximately 150 to 200 square feet of pavement. Coverage will vary depending on dilution rate, method of application and surface texture of the pavement to which it is applied.

Key Advantages

- Improves adhesion to any asphalt pavement
- Works with tree sap contamination
- Fast drying
- Works with oil and gasoline stains
- Prevents bleed through

Precautions:

ProBond may cause minor skin irritation. As with all chemicals, wear splash resistant goggles, protective gloves and clothing when handling. In case of skin or eye contact, immediately flush the area with clean water. Although it is an emulsion, vapors from *ProBond* are combustible. Use outdoors only in well ventilated areas. Keep away from heat, sparks and open flame. Do not breathe fumes, mist, vapors or spray. Consult Material Safety Data Sheet for more information on safety and handling.

Keep out of reach of children
For exterior use only
Close container when not in use

Combustible
Protect from freezing

Packaging:

5 gallon pails

Limited Warranty:

The Brewer Company warrants this product to be of merchantable quality when stored, used, and applied in accordance with the specifications and instructions herein. This Limited Warranty represents the sole and exclusive warranty. The Brewer Company's liability under this Limited Warranty is limited to replacement of the product proven defective, or at its option, refund of the purchase price.