



**DESCRIPTION**

#164 HOT APPLIED SEALANT is a mixture of asphalt, plasticizer, synthetic polymer, and reclaimed tire rubber.

An economical hot applied, one part sealant that provides superior results in concrete and asphaltic pavements.

- Good bonding characteristics
- Weather resistant
- Works well with both concrete and asphaltic pavements

**SPECIFICATIONS**

- ASTM D 1190
- ASTM D 6690, Type I
- AASHTO M 173
- AASHTO M 324, Type I
- FED SPEC SS-S-164
- FAA P-605

**TYPICAL PROPERTIES**

Recommended Pour Temperature.....	370° F- 390° F
Maximum Heating Temperature.....	400° F
Recommended Extended Heating.....	6 Hours
Penetration (150gr/5 sec).....	60 max
Softening Point.....	190° F min
Bond - -0° F/50% Ext.....	Passes 5 cycles
Asphalt Compatibility.....	Compatible

**USE AND APPLICATIONS**

#164 is recommended for sealing of joints and cracks in concrete and asphaltic pavements and parking lots. It is designed for use in sealing expansion and contraction joints as well as random cracks.

- Transverse joints
- Longitudinal joints

**FEATURES AND BENEFITS**

- Compound for concrete and asphaltic pavements
- Actually prolongs the pavement service life
- Seals cracks and joints from water penetration
- 100% solids

**PACKAGING**

60# CARTON (2 SPLIT 30# CUBES)  
36 CARTONS PER PALLET

35# CARTON  
60 CARTONS PER PALLET

30# NO BOX TRI-BLOCK UNIT  
65 UNITS PER PALLET



\*\*Patent Pending\*\*

**TECHNICAL SERVICE**

For conditions not specified, application procedures not noted, contact: Right Pointe Company (888) 755-5700.

**LIMITED WARRANTY**

Every reasonable effort is made to apply RIGHT POINTE COMPANY exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RIGHT POINTE COMPANY MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and RIGHT POINTE COMPANY shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the RIGHT POINTE COMPANY Technical Manager.

PRODUCT DATA SHEET #164