# SAFETY DATA SHEET

#### 1. Identification

Flex-a-Fill Products **Product identifier** 

Other means of identification Not available. Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company Name Crafco, Inc.

**Address** 420 North Roosevelt Avenue

Chandler, AZ 85226 USA

Telephone 602-276-0406

E-mail iim.chehovits@crafco.com

**Contact Person** Jim Chehovits

**Emergency 24-hour** 

1-800-424-9300 (CHEMTREC)

phone number

Information on operation 8:00a.m. - 5:00p.m.

hours

# 2. Hazard(s) identification

**Physical hazards** 

Not classified.

**Health hazards** 

Not classified.

**Environmental hazards** 

Not classified.

**OSHA** defined hazards Not classified.

\*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

#### **Label elements**

**Hazard symbol** 

None.

Signal word

Not applicable.

**Hazard statement** 

Not applicable.

Prevention Response

Not applicable.

Not applicable.

Storage

Not applicable.

Disposal

Not applicable.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	20 - 100
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0 - 40
Other components below reportable leve	ls		0 - 75

Composition comments

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

# 4. First-aid measures

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Inhalation

Get medical attention, if needed. Call a physician if symptoms develop or persist.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while Skin contact

removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes

before reuse.

Material name: Flex-a-Fill Products

SDS US 5972 Version #: 01 Issue date: 05-14-2015

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms/effects, acute and delayed Not available.

Indication of immediate medical attention and special treatment needed

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

# 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire may cause frothing.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases. Development of hazardous combustion gases or vapours possible in the event of a fire. The following may develop: Acrolein.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Runoff or release to sewer, waterway or ground is forbidden.

# 7. Handling and storage

Precautions for safe handling

The product is non-combustible. If heated, irritating vapors may be formed. Do not use in areas without adequate ventilation. Wash hands thoroughly after handling. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials. Keep out of the reach of children.

#### 8. Exposure controls/personal protection

### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	PEL	5 mg/m3	Mist.	

Material name: Flex-a-Fill Products

US. ACGIH Threshold Lim Components	it Values Type	Value	Form	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.	
US. NIOSH: Pocket Guide Components	to Chemical Hazards Type	Value	Form	
ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	Ceiling STEL TWA	5 mg/m3 10 mg/m3 5 mg/m3	Fume. Mist.	
Biological limit values	No biological exposure limits noted for	3.	Mist	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.			
Individual protection measure	es, such as personal protective equip	ment		
Eye/face protection	Wear safety glasses; chemical goggles (if splashing is possible). Wear chemical goggles; face shield (if handling molten material).			
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.			
Other	Wear suitable protective clothing and e	eye/face protection. Use of an	impervious apron is	

### Inc

recommended.

Skin protection

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards During product use, there is a risk of thermal burns.

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food

and drink. Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Appearance Solid. Physical state Solid. **Form** Solid.

Color Black, Dark brown

Odor Product is a black, semi-solid with a burnt tar odor.

**Odor threshold** Not available. Not available.

Melting point/freezing point 150 - 250 °F (65.56 - 121.11 °C) ASTM D36 Softening Point

Initial boiling point and

boiling range

> 800 °F (> 426.67 °C)

> 400.0 °F (> 204.4 °C) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit upper (%)

Not available.

Not available.

**Explosive limit - lower** (%)

**Explosive limit - upper** 

Not available.

(%)

Vapor pressure Vapor density

Not available. Not available.

Relative density Not available. Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature > 700 °F (> 371.11 °C)

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** Not Available

Percent volatile 0 % Specific gravity 1 - 1.9

### 10. Stability and reactivity

**Reactivity** Not available.

**Chemical stability** Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Strong oxidizing agents.

**Incompatible materials** Incompatible with oxidizing agents.

Hazardous decomposition

Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon monoxide, trace

**products** oxides of nitrogen and sulfur, and water.

# 11. Toxicological information

# Information on likely routes of exposure

**Ingestion** May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration.

**Inhalation** May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

**Skin contact** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Eye contact** May be irritating to eyes.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

# Information on toxicological effects

**Acute toxicity** Not classified.

**Skin corrosion/irritation** Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified.

# Respiratory or skin sensitization

**Respiratory sensitization** Not classified. **Skin sensitization** Not classified.

**Germ cell mutagenicity** Non-mutagenic based on Modified Ames Assay.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not classified.

**Chronic effects** Prolonged or repeated contact may cause drying, cracking, or irritation of the skin.

# 12. Ecological information

**Ecotoxicity**This product has no known eco-toxicological effects. Not expected to be harmful to aquatic

organisms.

Persistence and degradability Not available.

Material name: Flex-a-Fill Products
5972 Version #: 01 Issue date: 05-14-2015

Bioaccumulative potential

Not available.

Mobility in soil

Not available.

Other adverse effects

Not available.

# 13. Disposal considerations

**Disposal instructions** 

Dispose of contents/container in accordance with local/regional/national/international regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code

Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging

Offer rinsed packaging material to local recycling facilities.

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

**Further information** 

If the product is shipped at temperatures below 212°F (100°C), it is not regulated for transport by

ground, air or vessel. If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s.

(Asphalt mixture), 9, PG III"

# 15. Regulatory information

**US federal regulations** 

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4)

Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** 

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

No

**Hazardous chemical** 

# SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act** 

Not regulated.

(SDWA)

**US state regulations** 

WARNING: This product contains a chemical known to the State of California to cause cancer.

# **US. Massachusetts RTK - Substance List**

ASPHALT (CAS 8052-42-4)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

# **US. New Jersey Worker and Community Right-to-Know Act**

Not regulated.

Material name: Flex-a-Fill Products

SDS US

#### **US. Pennsylvania RTK - Hazardous Substances**

ASPHALT (CAS 8052-42-4)

### **US. Rhode Island RTK**

Not regulated.

# **US. California Proposition 65**

# US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4)

Listed: January 1, 1990

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

# 16. Other information, including date of preparation or last revision

Issue date

05-14-2015

Version #

**Further information** 

HMIS® is a registered trade and service mark of the NPCA.

References

**ACGIH** 

EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Material name: Flex-a-Fill Products

5972 Version #: 01 Issue date: 05-14-2015