Date Prepared: August 15, 2007

Keson Industries, Inc. 810 Commerce Street Aurora, IL 60504

MATERIAL SAFETY DATA SHEET

SECTION 1

Product Name: MARKING CHALK WHITE

For Information Call: 1-800-345-3766

SECTION II - Hazardous Ingredients of Mixture

Principal Component (s)	CAS #	OSHA PEL	ACGIH, TLV
Talc	14807-96-6	2 mg/m^3	2 mg/m^3
Quartz-Crystalline Silica	14808-60-7	0.1 mg/m^3	0.1 mg/m ³
Calcium Carbonate	471-34-1	15 mg/m ³	10 mg/m ³

SECTION III-Physical Data

Boiling Point: N/A Vapor Pressure: N/A % Volatile by weight: N/A Appearance: Odorless White Powder Specific Gravity (H2O=1) 2.6 Solubility in Water: Negligible Vapor Pressure: N/A pH 8.6-8.8 (Saturated Solution)

SECTION IV- Fire and Explosion Data

Flash Point:	Non-Flammable
Extinguishing Media:	Non-Flammable
Special Firefighting Procedures:	NIOSH Approved respirator and protective clothing should be worn. Use water spray to cool equipment and containers.
Unusual Fire Explosion Hazards:	None known.

SECTION V-Health Hazard Data

Routes of Entry: Skin-Yes, Inhalation-Yes, Ingestion-Yes, Eyes -Yes.

Carcinogenicity -Calcium Carbonate contains crystalline silica at levels between 0.01-2%. There is some evidence that this material may be carcinogenic. Limit exposure to the lowest limit possible.

Effects of Overexposure:Eye Contact-Irritating to eyesSkin Contact-None notedInhalation-May cause irritation to the nose, throat and respiratory tract.Ingestion-Harmful or fatal if swallowed.

SECTION V-Health Hazard Data (cont'd)

Emergency First Aid Procedures:

- Eye Contact: Flush with warm water, lifting the eyelids periodically for 15 minutes. Consult a physician if condition persists.
- Skin Contact: Wash affected area with warm soapy water. If irritation occurs, consult a physician.
- Ingestion: Call a physician immediately.
- Inhalation: Remove victim from dust area to fresh air and seek medical attention. Give artificial respiration if not breathing. Call a physician.

SECTION VI-Reactivity Data

Stability: Stable Conditions to avoid: None known.

Incompatibility (materials to avoid): Acids, aluminum, fluorine, magnesium, alum or ammonium salts

Hazardous Decomposition Products: Combustion will produce toxic oxides of carbon, calcium oxide.

Hazardous Polymerization: Will not occur.

SECTION VII-Spill or Leak Procedures

Vacuum or scoop material into approved containers for reclamation or disposal. If excessive dust is generated, wear NIOSH approved respirator for mineral dust.

SECTION VIII-Special Protection Information

Respiratory Protection:	An approved NIOSH respirator should be worn when TWA limits are exceeded.
Ventilation:	Use local ventilation to keep dust levels below recommended exposure limits. If exposure limits are exceeded, a NIOSH approved respirator for mineral dust should be worn.
Protective Clothing:	Employees must wear gloves.
Eye Protection:	Chemical safety goggles or safety glasses with splash guards.
Other Protective equipment:	Eye bath and safety shower should be available.

SECTION IX- Special Precautions

Precautions to be taken in handling and storage: Do not store near acids. Follow normal good housekeeping procedures.

Other Precautions: Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

SECTION X- Regulatory Status

TSCA Inventory Status: This material is a mixture, the ingredients of which are on TSCA inventory. RCRA: This material, when disposed of, is not specifically listed as a hazardous waste according to federal regulations unless it meets the USEPA definitions for being toxic, corrosive, ignitable or reactive, or it is mixed with or comes in contact with a listed hazardous waste. Consult local, state and federal regulations.

California Proposition 65: See Section XI SECTION XI-Other Regulatory Information

CHEMICAL NAME/ CAS NUMBER

CONCENTRATION

STATE CODE

Arsenic/7440-38-2 Cadmium/7440-43-9 Mercury/7439-97-6 Nickel/7440-02-0 Lead/7439-92-1 <100ppm* <5ppm* <1ppm* <400ppm* <100ppm* CA, MA CA, MA CA CA, MA CA

*Content of these materials may vary from batch to batch.

CA = California Proposition 65 MA = Massachusetts Hazardous Substance List

HMIS CODE:

Health1Flammability0Reactivity0

The information herein is given in good faith but no warranty, expressed or implied, is made.