



**Gator - Mastic**  
**Trowel Grade Crack Filler**

**Description:**

*Gator-Mastic* is designed for squeegee application to alligatored areas in asphalt pavements as a cost effective alternative to skin patching. *Gator-Mastic* is a blend of asphalt emulsion, select mineral fillers and plasticizers and is supplied ready to use. *Gator-Mastic* can also be used to fill shallow depressions or cracks over 1/2 inch in width in asphalt pavements.

**Application:**

*Gator-Mastic* must be applied only to cracks or alligatored areas that are clean, dry and free of debris and weeds. All vegetation must be treated with a water based herbicide at least one (1) week prior to crack sealing to prevent re-growth.

Use *Gator-Mastic* full strength. Do not dilute. Thoroughly mix *Gator-Mastic* prior to application. Work into alligatored areas and strike smooth with a rubber squeegee. Depressions can be filled in lifts no greater than 1/4 inch in thickness. Allow material to thoroughly dry before application of successive lifts. Fill cracks with *Gator-Mastic* flush to the pavement surface, removing any excess material with a squeegee or trowel. Allow *Gator-Mastic* to cure thoroughly before sealing or striping.

*Gator-Mastic* must be applied only when ambient and pavement temperatures are a minimum of 50 °F and are expected to remain there for at least eight (8) hours after application.

**Gator-Mastic Typical Properties:**

Property	Typical
Viscosity, dmm	320-400
Non-Volatile, %	67-72
Ash of Non-Volatile, %	48-52
Weight per Gallon	10.6-11.0
Ductility - ASTM D113	Pass
Adhesion & Water Resistance	No adhesion loss or blistering
Cured Color	Black

**Key Advantages**

- **Cost effective alternative to hot mix skin patching**
- **Ready to use**
- **Rubberized for improved flexibility**
- **Dark black color**

**Coverage:**

Approximately 20-30 square feet per gallon at 1/4 inch depth. For cracks, one gallon of *Gator-Mastic* will fill the following number of lineal feet:

Width	Depth		
	1/2"	3/4"	1"
1/2"	70	60	50
3/4"	60	50	40
1"	50	40	30

**Precautions:**

*Gator-Mastic* Trowel Grade Crack Filler may cause minor skin irritation. As with all chemicals, wear splash resistant goggles, protective gloves and clothing when handling *Gator-Mastic*. In case of skin or eye contact, immediately flush the area with clean water. Consult Material Safety Data Sheet for more information on safety and handling.

**Keep out of reach of children  
For exterior use only  
Close container when not in use**

**Protect from freezing  
Do not dilute  
Non-flammable**

**Packaging:**

5 gallon pails

**Limited Warranty:**

The Brewer Company warrants this product to be of merchantable quality when stored, used, and applied in accordance with the specifications and instructions herein. This Limited Warranty represents the sole and exclusive warranty. The Brewer Company's liability under this Limited Warranty is limited to replacement of the product proven defective, or at its option, refund of the purchase price.