



Brewer Cote[®] Crack Filler
Cold Pour Crack Filler

TECHNICAL BULLETIN

Description:

Brewer Cote[®] Cold Pour Crack Filler is a modified asphalt emulsion blend designed for filling cracks up to 1/4 inch in width in asphalt or concrete surfaces. It is formulated with a low viscosity for ease of installation and also contains aggressive adhesion promoters and tackifiers. It is intended to be a general purpose, cost effective crack repair sealant for remedying minor surface imperfections.

Application:

Brewer Cote[®] Cold Pour Crack Filler can be used to fill cracks up to 1/4 " in width, on either asphalt or concrete pavements. **Brewer Cote[®] Cold Pour Crack Filler** must be applied only to cracks that are clean, dry and free of debris and weeds. All vegetation must be treated with a water based herbicide at least one (1) week prior to crack sealing to prevent re-growth.

Use **Brewer Cote[®] Cold Pour Crack Filler** full strength. Do not dilute. Thoroughly mix **Brewer Cote[®] Cold Pour Crack Filler** prior to and during application. Fill the cracks with **Brewer Cote[®] Cold Pour Crack Filler**, making sure to squeegee any excess material flush with the pavement surface. Allow **Brewer Cote[®] Cold Pour Crack Filler** to cure before sealing or striping.

Brewer Cote[®] Cold Pour Crack Filler must be applied only when ambient and pavement temperatures are a minimum of 50 °F and are expected to remain there for at least eight (8) hours after application.

Brewer Cote[®] Crack Filler Typical Properties:

Property	Typical
Viscosity @ 77° F, cps	3,000 - 6,000
Non-Volatile, %	48 - 52
Ash of Non-Volatile, %	13-20
Flow @ 140 ° F, mm	< 5
Flexibility @ 32 ° F, 1" mandrel	No cracking, adhesion loss or blistering
Adhesion & Water Resistance	No adhesion loss or blistering
Cured Color	Black

Key Advantages

- Ready to use
- Modified for improved adhesion
- Low viscosity—readily flows into cracks of any size
- Economical, general purpose repair
- Dark black color

Coverage:

One gallon of **Brewer Cote[®] Cold Pour Crack Filler** will fill the following number of lineal feet:

Width	Depth	
	1/8"	1/4"
1/8"	1200	600
1/4"	600	300

Precautions:

Brewer Cote[®] Cold Pour Crack Filler may cause minor skin irritation. As with all chemicals, wear splash resistant goggles, protective clothing and gloves when handling. In case of skin or eye contact, immediately flush the area with clean water. Consult Material Safety Data Sheet for more information on safety and handling.

Keep out of reach of children **Protect from freezing**
For exterior use only **Do not dilute**
Close container when not in use **Non-flammable**

Packaging:

1 gallon pour spout jug (6 per case) and 5 gallon pails

Limited Warranty:

The Brewer Company warrants this product to be of merchantable quality when stored, used, and applied in accordance with the specifications and instructions herein. This Limited Warranty represents the sole and exclusive warranty. The Brewer Company's liability under this Limited Warranty is limited to replacement of the product proven defective, or at its option, refund of the purchase price.